



GECKO® 263 HEAVY DUTY PENETRATING OIL

FORMAT: AEROSOL

FEATURES

- Non-flammable
- Non-conductive
- Quickly penetrates
- Rust and corrosion protection
- Displaces moisture
- Dielectric strength: 39,000V
- Reduces wear caused by friction
- Does not contain silicone
- Safe to use on most sensible surfaces
- Non-drying, light, oily film
- Loosens rusted or frozen parts

Gecko® 263 is an industrial multi-purpose lubricant and penetrant formulated to displace moisture from electrical parts and ignition systems. **Gecko® 263** acts as a rust and corrosion preventive, leaving a non-drying film on metal surfaces that protects for up to one year indoors. It also improves the assembly and disassembly of machinery by providing long-lasting lubrication properties.

APPLICATIONS & USES

- Bearings & valves
- Engines and electric motor
- Frozen nuts and bolts
- Hand tools
- Mechanical Cables & linkages
- Metal parts
- Pulleys and rollers
- Slides and tracks
- Wet electrical systems

DIRECTIONS FOR USE

1. Shake well before using.
2. Spray liberal amount.
3. Reapply as needed.

PROPERTIES

Appearance / Physical State	Aerosol: Gas, Bulk: Liquid
Color	Brown
Dielectric Strength	39kV
Odor	Strawberry, slight petroleum odor
Propellant	Liquefied Gas
VOC Compliant CARB/OTC	No
Recyclable Packaging	Yes
Ozone Depleting Compounds	None



GECKO® 263 HEAVY DUTY PENETRATING OIL

SIZE / AVAILABILITY

Can Size: 16 oz

Net Weight: 15 oz

Quantity: 12 cans per case

HANDLING

Handle with care. This is a pressurized container, do not puncture or burn, even after use.

Do not use if the spray button is missing or damaged. Avoid spraying onto open flames, sparks, or any incandescent materials.

Do not smoke while applying this product or until treated surfaces are completely dry.

Keep containers away from cutting, welding, soldering, drilling, or grinding operations, and from all sources of heat or ignition.

Ensure that all handling equipment is properly grounded to prevent static discharge.

Do not reuse empty containers. Avoid prolonged or repeated skin contact.

Use only in well-ventilated areas and wear appropriate personal protective equipment.

Wash hands and exposed skin thoroughly after use and maintain good industrial hygiene practices.

STORAGE

Store in a cool, dry, well-ventilated, and secure area.

Pressurized container — protect from direct sunlight and do not expose to temperatures above 50°C (122°F).

Do not puncture, crush, or incinerate containers.

Keep away from open flames, heat, sparks, and other sources of ignition.

This product may accumulate static electricity that could cause a spark and ignite vapors.

Prevent electrostatic build-up through proper bonding and grounding procedures.

Keep containers tightly sealed in their original packaging.

Store away from incompatible materials (refer to Section 10 of the SDS).

Keep out of reach of children.

DISPOSAL

Dispose of contents and empty containers in accordance with local, regional, and national regulations.

Refer to the product's Safety Data Sheet (SDS) for specific disposal recommendations.

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see gecko2pro.com