



GECKO® 355 COPPER-BASED ANTI-SEIZE LUBRICANT

FORMAT: AEROSOL

FEATURES

- Brushes on easily
- Excellent adhesion and clinging properties
- Highly adhesive on both wet and dry surfaces
- Ideal for stainless steel and for joining dissimilar metals
- Lead-free formulation
- Lubricates, protects, and seals
- Allows reuse of fittings and easy removal or replacement of studs, bolts, and nuts
- Provides protection in high-temperature environments up to 2000°F (1093°C)
- Protects against heat-freeze, galling, rust, and corrosion
- Will not run, drip, or separate

Gecko®355 is a premium industrial grade heavy-duty copper fortified anti-seize lubricant formula that adheres, lubricates, protects, and seals. Excellent adhesion and water-repelling capabilities help to reduce torque and prevent galling, seizing, and galvanizing of metals.

Great for applications where extreme pressure and long-term protection are required and tough outdoor environmental conditions exist. Products will not melt, gum-up, or harden and is compatible with other lubricants.

APPLICATIONS & USES

- Bushings
- Chains
- Engines
- Flanges
- Heat Exchangers
- Manifolds
- Nuts & Bolts
- Screws
- Studs
- Turbines

DIRECTIONS FOR USE

1. Shake well before using.
2. Spray on all corroded, rusted or frozen parts.

Let's stand for several minutes to allow thorough penetration.

PROPERTIES

Appearance / Physical State	Aerosol: Gas, Bulk: Liquid
Color	Dark Green
Dielectric Strength	N/A
Odor	Solvent
Propellant	Liquefied Gas
VOC Compliant CARB/OTC	Yes
Recyclable Packaging	Yes
Ozone Depleting Compounds	None



GECKO® 355 COPPER-BASED ANTI-SEIZE LUBRICANT

SIZE / AVAILABILITY

Can Size: 20 oz

Net Weight: 15 oz

Quantity: 12 cans per case

Shipping Weight 17 Lb

HANDLING

Handle with care. This is a pressurized container, do not puncture or burn, even after use.

Do not use if the spray button is missing or damaged. Avoid spraying onto open flames, sparks, or any incandescent materials.

Do not smoke while applying this product or until treated surfaces are completely dry.

Keep containers away from cutting, welding, soldering, drilling, or grinding operations, and from all sources of heat or ignition.

Ensure that all handling equipment is properly grounded to prevent static discharge.

Do not reuse empty containers. Avoid prolonged or repeated skin contact.

Use only in well-ventilated areas and wear appropriate personal protective equipment.

Wash hands and exposed skin thoroughly after use and maintain good industrial hygiene practices.

STORAGE

Store in a cool, dry, well-ventilated, and secure area.

Pressurized container — protect from direct sunlight and do not expose to temperatures above 50°C (122°F).

Do not puncture, crush, or incinerate containers.

Keep away from open flames, heat, sparks, and other sources of ignition.

This product may accumulate static electricity that could cause a spark and ignite vapors.

Prevent electrostatic build-up through proper bonding and grounding procedures.

Keep containers tightly sealed in their original packaging.

Store away from incompatible materials (refer to Section 10 of the SDS).

Keep out of reach of children.

DISPOSAL

Dispose of contents and empty containers in accordance with local, regional, and national regulations.

Refer to the product's Safety Data Sheet (SDS) for specific disposal recommendations.

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see gecko2pro.com