



## GECKO® 766 HEAVY-DUTY SOLVENT DEGREASER

### FEATURES

- Emulsifiable
- Heavy-duty degreaser
- Dissolve tars, waxes & heavy greases
- Non-flammable
- Non-corrosive
- Metal-safe
- Environmentally safe

Emulsifiable heavy-duty degreaser with safe solvents for removing asphaltic greases, tank bottoms, crude residues, and more. Rapid penetration and strong emulsification for clean rinsing. Non-flammable, non-corrosive, metal-safe.

### DIRECTIONS FOR USE

1. Use as is
2. Apply evenly to the surface to be cleaned
3. Allow the product to act for approximately 45 seconds
4. Scrub with a brush or rinse with a pressure washer
5. If the surface remains dirty or greasy, repeat the procedure
6. Rinse and/or wipe any remaining residue
7. Always test for material compatibility on delicate or painted surfaces before full application

### APPLICATIONS & USES

- Oil extraction
- Industrial printing
- Manufacturing
- Mining
- Marine

### SIZE / AVAILABILITY

Pail 5 Gallons

Drum 55 Gallons

### PROPERTIES

Appearance / Physical State	Liquid
Color	Pink
Dielectric Strength	N/A
Odor	Solvent
Propellant	N/A
VOC Compliant CARB/OTC	No
Recyclable Packaging	Yes
Ozone Depleting Compounds	None



## GECKO® 766 HEAVY-DUTY SOLVENT DEGREASER

### HANDLING

Handle with care. Avoid spilling and splashing. Use only in well-ventilated areas.

Keep containers tightly closed when not in use. Do not handle, store, or open near flames, sparks, hot surfaces, or sources of ignition.

Do not cut, weld, solder, drill, or grind on or near containers. Ground and bond all transfer and handling equipment to prevent static discharge.

Avoid breathing vapors, mist, or spray. Avoid prolonged or repeated skin contact.

Use appropriate personal protective equipment (PPE) such as gloves, goggles, and protective clothing.

Wash hands thoroughly after handling and follow good industrial hygiene practices.

Do not reuse empty containers — they may contain product residues and should be properly rinsed and disposed of.

### STORAGE

Store in a cool, dry, well-ventilated, and secure area.

Pressurized container — protect from direct sunlight and do not expose to temperatures above 50°C (122°F).

Do not puncture, crush, or incinerate containers.

Keep away from open flames, heat, sparks, and other sources of ignition.

This product may accumulate static electricity that could cause a spark and ignite vapors.

Prevent electrostatic build-up through proper bonding and grounding procedures.

Keep containers tightly sealed in their original packaging.

Store away from incompatible materials (refer to Section 10 of the SDS).

**Keep out of reach of children.**

### DISPOSAL

Dispose of contents and empty containers in accordance with local, regional, and national regulations.

Refer to the product's Safety Data Sheet (SDS) for specific disposal recommendations.

### TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see [gecko2pro.com](http://gecko2pro.com)