



GECKO® 810 HEAVY DUTY SILICONE LUBE

FORMAT: AEROSOL

FEATURES

- Fine spray mist pattern
- Reduces friction and heat
- Repels dirt, dust, and grime
- Odorless and colorless
- Silicone-rich formulation
- Provides long-lasting lubrication and corrosion protection
- Wide operating temperature range: -58°F to 600°F (-50°C to 315°C)

Gecko® 810 is a clear, multi-purpose, heavy-duty silicone lubricant, release agent, and non-stick agent that eliminates sticking, binding, and squeaking while protecting rubber and plastic parts.

It is designed for use in the construction or manufacturing of goods such as automotive components, graphic arts, light manufacturing, furniture, and upholstery products.

It improves equipment longevity, enhances performance, and reduces downtime. Gecko® 810 is ideal for elastomers and plastics or applications where mineral or petroleum-based oils are not acceptable. For Industrial Use Only.

APPLICATIONS & USES

- Cables
- Castors
- Guards
- Guard Rails
- Moving Plastic Parts
- O-Rings
- Plastic Gears
- Plastic Rollers
- Rubber Bushings
- Rubber Mountings
- Seals
- Valves

DIRECTIONS FOR USE

1. Shake well before using.
2. Clean surface thoroughly.
3. Spray light film on surface.
4. If used on sticking parts, work back and forth and reapply.

PROPERTIES

Appearance / Physical State	Aerosol: Gas, Bulk: Liquid
Color	Colorless
Dielectric Strength	N/A
Odor	Odorless
Propellant	Liquefied Gas
VOC Compliant CARB/OTC	Yes
Recyclable Packaging	Yes
Ozone Depleting Compounds	None



GECKO® 810 HEAVY DUTY SILICONE LUBE

SIZE / AVAILABILITY

Can Size: 16 oz

Net Weight: 12.75 oz

Quantity: 12 cans per case

Shipping Weight 15 Lb

HANDLING

Handle with care. This is a pressurized container, do not puncture or burn, even after use.

Do not use if the spray button is missing or damaged. Avoid spraying onto open flames, sparks, or any incandescent materials.

Do not smoke while applying this product or until treated surfaces are completely dry.

Keep containers away from cutting, welding, soldering, drilling, or grinding operations, and from all sources of heat or ignition.

Ensure that all handling equipment is properly grounded to prevent static discharge.

Do not reuse empty containers. Avoid prolonged or repeated skin contact.

Use only in well-ventilated areas and wear appropriate personal protective equipment.

Wash hands and exposed skin thoroughly after use and maintain good industrial hygiene practices.

STORAGE

Store in a cool, dry, well-ventilated, and secure area.

Pressurized container — protect from direct sunlight and do not expose to temperatures above 50°C (122°F).

Do not puncture, crush, or incinerate containers.

Keep away from open flames, heat, sparks, and other sources of ignition.

This product may accumulate static electricity that could cause a spark and ignite vapors.

Prevent electrostatic build-up through proper bonding and grounding procedures.

Keep containers tightly sealed in their original packaging.

Store away from incompatible materials (refer to Section 10 of the SDS).

Keep out of reach of children.

DISPOSAL

Dispose of contents and empty containers in accordance with local, regional, and national regulations.

Refer to the product's Safety Data Sheet (SDS) for specific disposal recommendations.

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see gecko2pro.com