



GECKO® 815 CHAIN & CABLE LUBRICANT WITH MOLY

FORMAT: AEROSOL

FEATURES

- Thick foaming action evenly coats the surface
- Forms a protective lubricating barrier
- Effective temperature range: 10°F to 400°F
- Contains molybdenum disulfide (MoS₂)
- Extends chain and wire rope service life
- Performs under extreme pressure and temperature conditions
- Water-displacing solvents penetrate cracks and the wire rope core quickly
- Anti-sling adhesion reduces mess during operation
- Reduces wear caused by friction and corrosion
- Provides maximum lubrication and corrosion protection

Gecko® 263 is an industrial multi-purpose lubricant and penetrant formulated to displace moisture from electrical parts and ignition systems. **Gecko® 263** acts as a rust and corrosion preventive, leaving a non-drying film on metal surfaces that protects for up to one year indoors. It also improves the assembly and disassembly of machinery by providing long-lasting lubrication properties.

APPLICATIONS & USES

Gecko® 815 is an industrial-grade molybdenum disulfide lubricant formulated to penetrate parts exposed to corrosive elements, providing protection against friction and wear.

This chain and cable lubricant features thick foam that clings and coats evenly, offering heavy-duty resistance to wear. It forms a protective rust barrier and provides extreme pressure and load-carrying capabilities that will not break down under elevated temperatures.

It is designed for use on roller chains, wire ropes, cables, and other industrial components.

DIRECTIONS FOR USE

1. Shake vigorously for one minute after mixing ball begins to rattle.
2. Spray 8-10 inches from surface.
3. Allow it to penetrate.
4. The second coat gives additional protection.

PROPERTIES

Appearance / Physical State	Aerosol: Gas, Bulk: Liquid
Color	Dark Green
Dielectric Strength	N/A
Odor	Solvent
Propellant	Liquefied Gas
VOC Compliant CARB/OTC	Yes
Recyclable Packaging	Yes
Ozone Depleting Compounds	None



GECKO® 815 CHAIN & CABLE LUBRICANT WITH MOLY

SIZE / AVAILABILITY

Can Size: 20 oz

Net Weight: 15 oz

Quantity: 12 cans per case

Shipping Weight 17 Lb

HANDLING

Handle with care. This is a pressurized container, do not puncture or burn, even after use.

Do not use if the spray button is missing or damaged. Avoid spraying onto open flames, sparks, or any incandescent materials.

Do not smoke while applying this product or until treated surfaces are completely dry.

Keep containers away from cutting, welding, soldering, drilling, or grinding operations, and from all sources of heat or ignition.

Ensure that all handling equipment is properly grounded to prevent static discharge.

Do not reuse empty containers. Avoid prolonged or repeated skin contact.

Use only in well-ventilated areas and wear appropriate personal protective equipment.

Wash hands and exposed skin thoroughly after use and maintain good industrial hygiene practices.

STORAGE

Store in a cool, dry, well-ventilated, and secure area.

Pressurized container — protect from direct sunlight and do not expose to temperatures above 50°C (122°F).

Do not puncture, crush, or incinerate containers.

Keep away from open flames, heat, sparks, and other sources of ignition.

This product may accumulate static electricity that could cause a spark and ignite vapors.

Prevent electrostatic build-up through proper bonding and grounding procedures.

Keep containers tightly sealed in their original packaging.

Store away from incompatible materials (refer to Section 10 of the SDS).

Keep out of reach of children.

DISPOSAL

Dispose of contents and empty containers in accordance with local, regional, and national regulations.

Refer to the product's Safety Data Sheet (SDS) for specific disposal recommendations.

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see gecko2pro.com