



GECKO® 816 DRY MOLY LUBRICANT

FORMAT: AEROSOL

FEATURES

- Fast drying
- Thin film
- Fortified molybdenum disulfide
- Non-corrosive
- Oil-free formula
- Perform well at high temperatures from -28°F to 600°F
- Methylene chloride free
- Repel dust and dirt
- Prevents seizure of parts

Gecko® 816 is formulated with molybdenum disulfide for superior anti-friction and anti-seize performance under extreme conditions.

This heavy-duty industrial lubricant adheres strongly to most surfaces while repelling dust and dirt.

Gecko® 816 is free of methylene chloride and improves operating efficiency while reducing maintenance costs by resisting corrosion caused by water, alkalis, and acids.

It is designed for use in areas exposed to high temperatures (-28°F / -33°C to 600°F / 315°C) and high-pressure conditions.

DIRECTIONS FOR USE

1. Shake vigorously for one minute after mixing ball begins to rattle. Clean surface thoroughly.
2. Hold can 6 to 8 inches from surface and apply evenly.
3. Allow 1 to 5 minutes for adequate drying.
4. Shake vigorously and often.
5. Before storage turn the can upside down and spray until clear.

APPLICATIONS & USES

- Aircraft landing gear components
- Brake adjustment screws and mechanisms
- Forklift masts and guide channels
- Fire door hinges and tracks
- Oven chains and wire cables
- Oven dollies and conveyors
- Overhead crane rails and hoist systems
- Oven hooks and support hanger

PROPERTIES

Appearance / Physical State	Aerosol: Gas, Bulk: Liquid
Color	Dark
Dielectric Strength	N/A
Odor	Solvent
Propellant	Liquefied Gas
VOC Compliant CARB/OTC	No
Recyclable Packaging	Yes
Ozone Depleting Compounds	None



GECKO® 816 DRY MOLY LUBRICANT

SIZE / AVAILABILITY

Can Size: 16 oz

Net Weight: 11 oz

Quantity: 12 cans per case

Shipping Weight 13 Lb

HANDLING

Handle with care. This is a pressurized container, do not puncture or burn, even after use.

Do not use if the spray button is missing or damaged. Avoid spraying onto open flames, sparks, or any incandescent materials.

Do not smoke while applying this product or until treated surfaces are completely dry.

Keep containers away from cutting, welding, soldering, drilling, or grinding operations, and from all sources of heat or ignition.

Ensure that all handling equipment is properly grounded to prevent static discharge.

Do not reuse empty containers. Avoid prolonged or repeated skin contact.

Use only in well-ventilated areas and wear appropriate personal protective equipment.

Wash hands and exposed skin thoroughly after use and maintain good industrial hygiene practices.

STORAGE

Store in a cool, dry, well-ventilated, and secure area.

Pressurized container — protect from direct sunlight and do not expose to temperatures above 50°C (122°F).

Do not puncture, crush, or incinerate containers.

Keep away from open flames, heat, sparks, and other sources of ignition.

This product may accumulate static electricity that could cause a spark and ignite vapors.

Prevent electrostatic build-up through proper bonding and grounding procedures.

Keep containers tightly sealed in their original packaging.

Store away from incompatible materials (refer to Section 10 of the SDS).

Keep out of reach of children.

DISPOSAL

Dispose of contents and empty containers in accordance with local, regional, and national regulations.

Refer to the product's Safety Data Sheet (SDS) for specific disposal recommendations.

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see gecko2pro.com