



# GECKO® 817 DRY FILM GRAPHITE LUBRICANT

## FORMAT: AEROSOL

### FEATURES

- Bonds instantly to metal, rubber, and plastic substrates
- Fast drying & high adhesive strength
- Resists water, oils, and alkalis
- Heat stable from -100°F to 850°F

**Gecko®817** is a fast drying, super-adhesive film lubricant fortifies with graphite that coats and protects metals and plastics.

Extends the life of moving parts while providing superior lubrication that is resistant to water, oils, and chemical attack without attracting dust and dirt. Performs well in extreme pressures and temperatures creating a protective barrier that reduces metal wear and fatigue.

Exceptional on aluminum, brass, copper, titanium, steel alloys and cast iron.

### DIRECTIONS FOR USE

1. Shake vigorously for one minute after mixing ball begins to rattle.
2. Spray at 8 to 12 inches distance spraying a light even film.
3. Wipe off excess with a cloth.
4. Repeat application, the second coat gives additional protection.
5. For personal safety, do not use it while the equipment is energized.

## APPLICATIONS & USES

- Bearings, chains and hinges,
- Engine assembly
- Industrial gaskets
- Wheels, gears and chains
- Plant machinery
- Handling equipment
- High temperature equipment

## PROPERTIES

Appearance / Physical State	Aerosol: Gas, Bulk: Liquid
Color	Black
Dielectric Strength	N/A
Odor	Solvent
Propellant	Liquefied Gas
VOC Compliant CARB/OTC	Yes
Recyclable Packaging	Yes
Ozone Depleting Compounds	None



## GECKO® 817 DRY FILM GRAPHITE LUBRICANT

### SIZE / AVAILABILITY

Can Size: 16 oz

Net Weight: 12.75 oz

Quantity: 12 cans per case

Shipping Weight 15 Lb

### HANDLING

Handle with care. This is a pressurized container, do not puncture or burn, even after use.

Do not use if the spray button is missing or damaged. Avoid spraying onto open flames, sparks, or any incandescent materials.

Do not smoke while applying this product or until treated surfaces are completely dry.

Keep containers away from cutting, welding, soldering, drilling, or grinding operations, and from all sources of heat or ignition.

Ensure that all handling equipment is properly grounded to prevent static discharge.

Do not reuse empty containers. Avoid prolonged or repeated skin contact.

Use only in well-ventilated areas and wear appropriate personal protective equipment.

Wash hands and exposed skin thoroughly after use and maintain good industrial hygiene practices.

### STORAGE

Store in a cool, dry, well-ventilated, and secure area.

Pressurized container — protect from direct sunlight and do not expose to temperatures above 50°C (122°F).

Do not puncture, crush, or incinerate containers.

Keep away from open flames, heat, sparks, and other sources of ignition.

This product may accumulate static electricity that could cause a spark and ignite vapors.

Prevent electrostatic build-up through proper bonding and grounding procedures.

Keep containers tightly sealed in their original packaging.

Store away from incompatible materials (refer to Section 10 of the SDS).

**Keep out of reach of children.**

### DISPOSAL

Dispose of contents and empty containers in accordance with local, regional, and national regulations.

Refer to the product's Safety Data Sheet (SDS) for specific disposal recommendations.

### TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see [gecko2pro.com](http://gecko2pro.com)